

Single Tube Multi-core armored optical fiber cables

Features

- Good mechanical and environmental characteristics
- Soft, Flexible, Stable, easy to splice, rat bite protection, Apply to connections of long distance, outdoor, building cabling, combination cabling of fiber optic and electronic
- Flame retardant characteristics meet the requirements of relevant standards
- Improve existing function based on customers' various requirements

Specifications

Cable Type	Cable diameter (mm)	Cable weight (Kg/KM)	Tensile N		Bend radius		Crush (N/100mm)
			short term	long term	dynamic	static	
3.0GJFKV-6S	Φ3.0±0.2	12.5	400	200	60	30	3500
3.0GJFKV-8S	Φ3.0±0.2	12.7	800	400	70	35	3000
3.0GJFKV-12S	Φ3.0±0.2	13.0	1000	500	90	45	3000
4.5GJFKV-4S	Φ4.5±0.2	27.5	800	400	70	35	3000
4.8GJFKV-6S	Φ4.8±0.2	32.5	1000	500	100	50	3000
4.8GJFKV-8S	Φ4.8±0.2	36.0	1000	500	100	50	3000
5.0GJFKV-10S	Φ5.0±0.25	42.0	1000	500	120	60	3000
6.0GJFKV-12S	Φ6.0±0.20	61.0	1500	750	170	85	3000

