



Specification

SC Clamshell Adapter

Description

Fiber optic adapter is to achieve the same or different optical fiber connectors docking in optical links, make the light path connected under the small loss. It is to put the fiber of two surface precision docking, so that the optical output of light energy to the maximum coupling in the receiving optical fiber, and since it entered the optical link to minimize the effects on the system. Widely used in optical fiber distribution frame (ODF), fiber optic communications equipment, instruments, etc., superior performance, stable and reliable.

Application

- CATV
- Telecommunication networks
- Local Area Networks (LANs)
- Data processing networks
- Test equipment
- Premise installations
- Gigabit Ethernet
- Metro

Features


- Low insertion loss and back reflection loss
- High precision alignment
- Compact design
- With/Without flange
- Choice of housing material and sleeve material
- Telcordia, ANSI, TIA/EIA, NTT and JIS compliance

Specification

Item	Specification
Insertion Loss	<0.20dB
Durability	<0.20dB typical change, 1000 matings
Operating Temperature	-40 ~ 85°C(PBT) / -25 ~ 70°C(ABS)

Availability


Type	Structure Type	Flange Type	Cover Type	Housing Color
Outer Clamshell	Simplex	Flange	Detachable Clamshell	SM/PC - Blue SM/APC - Green
	Duplex	No Flange	Non-detachable Clamshell	MM/PC - Beige/Aqua/Magenta/Black
Inner Clamshell	Simplex	Flange	Non-detachable Clamshell	SM/PC - Blue SM/APC - Green
		No Flange		MM/PC - Beige/Aqua/Magenta/Black



Outer Clamshell



Inner Clamshell



Detachable Clamshell



Non-detachable Clamshell

