



Specification

MPO Connector

Features

- IEC 61754-7 Compliant
- Compact design, up to 24 fiber ribbon
- Polishing does not require diamond film
- Precision molded MT ferrule
- Telcordia GR-1435-CORE compliant
- Low insertion loss and back reflection loss
- High precision guide pins for exact alignment

Application

- CATV, and Multimedia
- Gigabit Ethernet
- Industrial and medical
- Active device interface
- Premise installations
- Interconnection for O/E modules
- Data processing networks
- Telecommunication networks
- Optical switch interframe connection
- Asynchronous Transmission Mode (ATM)

Availability

- 12/16/24F MT ferrule
- Single mode/Multimode
- Round/Flex/Bare boot type
- Low loss/standard loss
- Male/female

Specification



Item	Single Mode(APC)	Multimode(PC)
Insertion Loss	12/16/24F standard loss \leq 0.75dB 12/16F low loss \leq 0.35dB 24F low loss \leq 0.5dB	12/16/24F standard loss \leq 0.75dB 12/16F low loss \leq 0.35dB 24F low loss \leq 0.5dB
Return Loss	\geq 60dB	\geq 20dB
Durability	<0.3dB typical change, 200 matings	<0.3dB typical change, 200 matings
Operating Temperature	-40°C ~ 85°C	-40°C ~ 85°C